


# DGL-Y03 Bollard Light

<b>Catalog #</b>		<b>Prepared by</b>	LiteHarbor
<b>Project</b>		<b>Date</b>	
<b>Notes</b>			



## Bollard Light

### Description

- 1) The stainless steel bollard is constructed of 316 marine grade stainless steel and is cold worked for superior corrosion resistance
- 2) Ideal for harsh environments and where corrosion is common
- 3) Choose from 4 head styles: 360°open head,180°open head 360°slotted head and 180°slotted head.
- 4) Provides uniform illumination and superior brightness control. Ideal for courtyards providing a safe ambient lighting

### Features

- 1) Prewired integral driver for ease of installation.
- 2) Driver is mounted to a stainless steel hanger bracket directly below the lamp.
- 3) Tamper proof set screws for re-lamp access
- 4) Easy to maintain impact resistant long-life polished stainless steel.
- 5) Conical upper reflector for optimal light distribution
- 6) UV stabilized 25"thick polycarbonate frosted lens
- 7) Available in 24",32"or 42"height.

Confirm with factory for other lengths

### Anchor Base

Bollard base is secured by three 3 internal heavy-duty stainless steel rods

Mounts to three stainless steel anchor bolts ,each with two nuts and washers.

### Order Matrix

A    B    C    D    E    F

#### Item No.DGL-Y03

A	Series
Y0301	180° Open Head Bollard Light
Y0302	360° Open Head Bollard Light
Y0303	180° Slotted Head Bollard Light
Y0304	360° Slotted Head Bollard Light

B	Material & Finish
ST6	316 stainless steel
ST4	304 stainless steel
BK	Aluminum/black
WH	Aluminum/white
SV	Silver

C	Input
	120V
##	277V

D	Lamp
TRT	TRT/Fluorescent
DTT	DTT/Fluorescent
T6	T6/Metal Halide

BOLLARDLIGHT



**Liteharbor Lighting Technology Co., Ltd.**  
New Industry Area Hecun Danzao Town  
Nanhai Foshan City Guangdong China

TEL: +86-757-8180 8687  
FAX: +86-757-8180 8685  
E-mail: sales@liteharbor.com

Website: www.liteharbor.com  
Specifications subject to change w/o notice  
Revision: Jan. 2013

# DGL-Y03 Bollard Light

Catalog #		Prepared by	LiteHarbor
Project		Date	
Notes			

Anchor kit supplied with fixture.  
Includes a stainless steel leveling bracket/template.

## Lamp Enclosure

Bollard top is easily removed for re-lamping and ballast accessibility.

Secured by three tamper-proof stainless steel set screws.

Weather-tight frosted UV stabilized polycarbonate lens with rubber gaskets completely seals unit.

## Maintenance:

Stainless steel requires regular dealing and maintenance to prevent tarnishing or tea staining.

## Electrical

### 1)LED

13W max

Recommend 6W high brightness

Life time:>50000 hours

Current 700Ma driver

Input: 100-240V

50/60Hz

Output:Max 12V DC

### 2) Metal Halide

20W T6 CMH

39W T6 CMG

G12 Base

120-277V HPF electronic ballast with inherent thermal protection

Sound rated A

Minimum ballast temp -15°C/5°C.

Harmonic distortion<20%

Outdoor type 1

Increased reliability and safety with lamp "Turn-off Function"

### 3) Compact Fluorescent

13W DTT

18/26W TRT

GU24 Universal Socket

Advance ballast

Inherent thermal protection

E	Light Source & Wattage
L13	LED 13W max
M39	Metal Halide 39W max
F26	Compact fluorescent 26W max

F	Available
EM	Emergency System

Other Special Requirements please Confirm with Factory



BOLLARDLIGHT



**Liteharbor Lighting Technology Co., Ltd.**

New Industry Area Hecun Danzao Town

Nanhai Foshan City Guangdong China

TEL: +86-757-8180 8687

FAX: +86-757-8180 8685

E-mail: sales@liteharbor.com

Website: www.liteharbor.com

Specifications subject to change w/o notice

Revision: Jan. 2013

# DGL-Y03 Bollard Light

Catalog #		Prepared by	LiteHarbor
Project		Date	
Notes			

High power factor  
 Sound rated A  
 Class P minimum ballast temp -18°C/0°F  
 Harmonic distortion<10%  
 Outdoor type 1



BOLLARDLIGHT



**Liteharbor Lighting Technology Co., Ltd.**  
 New Industry Area Hecun Danzao Town  
 Nanhai Foshan City Guangdong China

TEL: +86-757-8180 8687  
 FAX: +86-757-8180 8685  
 E-mail: sales@liteharbor.com

Website: www.liteharbor.com  
 Specifications subject to change w/o notice  
 Revision: Jan. 2013