


Catalog #		Prepared by	LiteHarbor
Project		Date	
Notes			



ORDER MATRIX | Example: G4011-B

<u>A</u>	<u>B</u>	<u>C</u>	<u>D</u>	<u>E</u>
A	Series			
G4011-B	1-Lamp			
G4012-B	2-Lamp			
G4013-B	3-Lamp			
G4014-B	4-Lamp			
G4014-B-S	4-Lamp			
B	Input Voltage			
	120V			
277	277V			
U	120-277V			
C	LED Available			
Cree	Cree			
Citizen	Citizen			
Epistar	Epistar			
Seoul	Seoul			
Osram	Osram			

Description

Easy Installation and maintenance

All parts and components accessible from below the ceiling
Lamp holders are adjustable 360 °horizontal and 30 °vertical for spot lighting in multiple directions

Actual adjustment may vary depending on the lamp beam spread

Housing

The inner trim is constructed of 22GA steel

Finish can be black, white or silver

Special finish please confirm with factory

Internal wire bundles are locked and covered with a glass sleeve

Junction box can be accessible from below the ceiling with a plate

Mounting Frame

Can accommodate a 1/2" to 1 1/4" ceiling thickness

Channel bracket allow up to 5" vertical adjustable

Universal mounting brackets included

Compatible with C-channel, flat bar, and EMT

C-channel are recommended for T-bar ceilings

Bar hangers must be ordered separately



MULTIPLE DOWNLIGHT



Liteharbor Lighting Technology Co., Ltd.

New Industry Area Hecun Danzao Town

Nanhai Foshan City Guangdong China

TEL: +86-757-8180 8675

FAX: +86-757-8180 8685

E-mail: info@liteharbor.com

Website: www.liteharbor.com

Specifications subject to change w/o notice

Revision: Jan. 2015

D	Color Temperature
27K	2700K
30K	3000K
35K	3500K
41K	4100K

E	Optics
12°	12° spot
24°	24° narrow flood
36°	36° flood

Flanged Trim

Extruded trim frame includes torsion springs for convenient installations or removal from the housing

Trimless

Optional mud frame available for trimless mounting
The perforated mesh frame provided adheres to joint compound for seamless and trimless mounting

LED Light Engine

2700k-4100k

CRI>80%

LED mounted to die-cast/extruded aluminum heat sink
50000 hours average rated life at 70% lumen

Electrical System

120-277V input

Class 2 power supply

Over voltage, over current and short circuit protection

Auto recovery

10% dimmable is available 120V only

10/15/17.8/20W each lamp

Light Efficiency:70-80lm/W(Consult with our factory)

Lamp Q'ty (PCS)	Wattage (W)	Lumen (LM)	Color Temperature (K)
1 lamp	20W	1400LM	2700K-4100K
2 lamps	40W	2800LM	
3 lamps	60W	4200LM	
4 lamps	80W	5600LM	
4 lamps square	80W	5600LM	



Liteharbor Lighting Technology Co., Ltd.

New Industry Area Hecun Danzao Town

Nanhai Foshan City Guangdong China

TEL: +86-757-8180 8675

FAX: +86-757-8180 8685

E-mail: info@liteharbor.com


Website: www.liteharbor.com

Specifications subject to change w/o notice

Revision: Jan. 2015



Size



1x2 SPOTS

L: 21 1/8"xW: 8 9/16"xH: 8 11/16"
Cut-Out(axb): 11 1/4" x 6 1/4"

1x1 SPOTS

L: 15 7/8"xW: 8 9/16"xH: 8 11/16"
Cut-Out(axb): 6 1/4" x 6 1/4"

1x3 SPOTS

L: 26 1/4"xW: 8 9/16"xH: 8 11/16"
Cut-Out(axb): 16 5/8" x 6 1/4"

1x4 SPOTS

L: 31 5/16"xW: 8 9/16"xH: 8 11/16"
Cut-Out(axb): 21 3/4" x 6 1/4"

2x2 SPOTS

L: 21"xW: 13 3/4"xH: 8 11/16"
Cut-Out(axb): 11 7/16" x 11 7/16"