
Catalog #



ORDER MATRIX | Example: G4011-C

В	Input Voltage
	120V
277	277V
U	120-277V

С	Dimmable
	Non-Dimmable
DM	Dimmable

D	Wattage
30	30W
40	40W

## Description

RGBW state of the art down light

Compatible with 512 universal controllers in the market The floating head permits trim adjustable of angles and direction Imagine creating ANY COLOR your mood desires just by press of Regular lighting/ Reading mode/ Color changing/ Party mode DMX 512 controller needed. Sold separately

## **Application**

High end residence and Commercial applications

Hotel

Casino

Photo Studio

Art gallery

Film studio

Film set


5-year warranty

ETL,UL,CCC,CE,TUV,RoHs,Fcc

5 Years

E	Туре	Technical I	nfo		
RGB	RGB	DMX decoder	512/1990 Standard	12/24VDC	
RGBW	RGBW	512DMX	256 levels	4 channels	
CW	CW=5000K		85~240VAC/12VDC	UL Listed	
WW	WW=2700K	LED Driver	5 years warranty	MeanWell/Rico	
	•		40W RGBW	Individually addressable channels	
F	Trim		9x9mm	Extreme Lm density	
Т	Trimmed	DCDW Cl. in	COB	Low Thermal resistance	
TL	Trimless	RGBW Chip	Glass lens	Level 1 moisture sensitivity	
G	Optics		MCPCB Available	Compatible with high Uniformity mixing lenses	
12°	12° spot		Trim-less or trimmed	UL/ETL Listed	
24°	24° narrow flood		0.5mm thick gauge	4"device" compartments for	
36°	36° flood		Aluminum/steel sheet	electrical equipment	Litcharbo
54°	54° flood	Fixture	High grade	Swivel in all directions floating head	i

Size



1x1 SPOTS

Certificate

Warranty

1/2"UL standard

Knockouts

L: 9"xW: 12 3/16"xH: 7 9/16" Cut-Out(axb): 7 9/16" x 7 9/16"

iteharbor Lighting Technology Co., Ltd.

[ew Industry Area Hecun Danzao Town
Liteharbor | Janhai Foshan City Guangdong China

TEL: +86-757-8180 8675 FAX: +86-757-8180 8685

E-mail: info@liteharbor.com

Website: www.liteharbor.com

Specifications subject to change w/o notice

Revision: Jan. 2015