





ORDER MATRIX | Example: A6R-VA

Example: //erc //					
_A	_B	С	D	_ <u>E</u> _	
			<u> </u>		
Α	Series				
A6R-VA	6" Architectural Vertical Remodel Housing				
	I				
В	Input Voltage				
	120V				
277	277V				
U	120-277	V			
С	Lamp				
P30 P38	PAR30 PAR38				
A19	A19				
A21	A21				
7121	/ 12 !				
D	Wattage				
L18	18W				
L24	24W				
L12	12W				
L17	17W				
_	I				
E		mperature	!		
28K	2800K				
35K	3500K				
50K	5000K				
65K	6500K				

6" Architectural Vertical Remodel Housing





Mounting

- > Constructed from 16-gauge steel, die-formed construction for max heat dissipation and rust protection
- > Precision tooled springs secure trim to mounting frame for effortless and tool-less installation
- > Fully assembled for ease of installation
- > Non-IC housing require a minimum clearance of 3" around from thermal insulation and 1/2" from combustible material from above the fixture

Junction Box

- Pre-wired junction box provided with 1/2" and 3/4" knockouts, romex knockouts with pry-out slots and strain clamps
- > Provided with removable access plates
- All leads are #18AWG wire, the ground wire connected to the bottom and quick connectors are supplied on all leads
- > Through branch circuit wiring (4 in, 4 out)

Socket Cup

- > Adjusts vertically for optimum light performance
- > Die-cast fin construction for heat dissipation
- $\,\,\boldsymbol{\succ}\,\,$ Unitized optics guarantees proper trim to housing installation
- $\,>\,$ Tool-less installation adjustability from either outside the housing or inside the housing

Reflector

- ➤ High quality reflector with 1.2mm thickness available
- > Optional painted white flange is available

Thermal Protector

- Meet ETL requirements
- Standard thermal protection device guards against improper installation, over lamping and misuse of insulation material
- > External thermal device located on the junction box wrap

Socket

➤ E26 medium base

Lamp

- ➤ LED PAR30 18W max.
- ➤ LED PAR38 24W max.
- ➤ LED A19 12W max.
- > LED A21 17W max.
- > CRI>80%
- ➤ PF>0.9
- ➤ Color Temperature: 2800K-6500K

Listing

> ETL listed for damp location W/Feed through





RV6002

6 inch Vertical Reflector Self Flanged/White Ring



RC602 6 inch Vertical Reflector with Regressed Lens



RC603

6 inch Vertical Baffle with Regressed Lens Self Flanged/White Ring



RC608

6 inch Vertical Cross Blade White Ring



RV612

6 inch Vertical Reflector with Baffle White Ring



RC166

6 inch Vertical Reflector with Drop Glass Self Flanged

11 www.liteharbor.com