


6 inch Fluorescent Commercial Housing

| | | | |
|------------------|--|--------------------|------------|
| Catalog # | | Prepared by | LiteHarbor |
| Project | | Date | |
| Notes | | | |



6" Fluorescent Horizontal Commercial Housing

Mounting

- 1) Constructed from 16-gauge steel
- 2) Fram includes bar hangers with nails for wood joist
- 3) Installed spring steel friction clips
- 4) Adjustable 14"-25" for precise placement
- 5) Bar hangers include T-bar notch for T-grid ceiling installations
- 6) Fully assembled for ease of installation
- 7) Must be kept at least 3" away from insulation

Junction Box

- 1) Pre-wired junction box provided with 1/2" and 3/4" knockouts
- 2) Provided with removable access plates
- 3) Knockouts equipped with pryout slots
- 4) All leads are #18AWG wire, the ground wire connected to the bottom and quick connectors are supplied on all leads
- 5) Through branch circuit wiring(4 in, 4 out)

Reflector

- 1) High quality reflector with 1.2mm thickness available in multiple architectural finishes and types.
- 2) Optional painted white flange is available

Order Matrix

| A | B | C | D | E |
|-------------------|----------------------------------|--------------------------------|---|---|
| A Series | | | | |
| AF6-CE-HC | 6" Horizontal Commercial Housing | Fluorescent | | |
| B Ballast | | | | |
| | | No Ballast | | |
| | | E Electronic Ballast | | |
| | | DE Dimmable Electronic Ballast | | |
| C Input Voltage | | | | |
| | | 120V | | |
| | | ## 277V | | |
| D Wattage | | | | |
| F26 | | CFL 26W | | |
| F32 | | CFL 32W | | |
| F213 | | CFL 2*13W | | |
| F218 | | CFL 2*18W | | |
| F226 | | CFL 2*26W | | |

COMMERCIAL HOUSING



Liteharbor Lighting Technology Co., Ltd.
 New Industry Area Hecun Danzao Town
 Nanhai Foshan City Guangdong China

TEL: +86-757-8180 8675
 FAX: +86-757-8180 8685
 E-mail: info@liteharbor.com

Website: www.liteharbor.com
 Specifications subject to change w/o notice
 Revision: Jan. 2015

3) Single position optics eliminate possibility of specified lamp being installed in incorrect position

Ballast

- 1) Thermally protected
- 2) Electronic ballast provide full light output and rated lamp life
- 3) Flicker free and noise free operation and starting
- 4) End of lamp life protection is standard
- 5) Attached to junction box cover so it may be serviced from below the ceiling no tools required

Socket

Universal G24 4-pin

Lamp

2*13/2*18/2*26W 4 pin

Universal G24 4-PIN

CRI>80%

PF>0.9

Color Temperature:2800K-6500K

Listing

ETL listed for damp location W/Feed through

| E | Color Temperature |
|-----|-------------------|
| 28K | 2800k |
| 35K | 3500K |
| 50K | 5000K |
| 60K | 6000K |

Special Requirements Confirm with Factory



Liteharbor Lighting Technology Co., Ltd.

New Industry Area Hecun Danzao Town
Nanhai Foshan City Guangdong China

TEL: +86-757-8180 8675

FAX: +86-757-8180 8685

E-mail: info@liteharbor.com

Website: www.liteharbor.com

Specifications subject to change w/o notice

Revision: Jan. 2015



RH6002
6 inch Horizontal Reflector
Self Flanged/White Ring



RC611
6 inch Horizontal Reflector with
Baffle
White Ring



RC612
6 inch Horizontal Reflector with
Regressed Lens
Self Flanged/White Ring



RC613
6 inch Horizontal Baffle with
Regressed Lens
White Ring



RC614
6 inch Horizontal Cross Blade
White Ring



RCH166
6 inch Horizontal Reflector with
Drop Glass
Self Flanged



Liteharbor Lighting Technology Co., Ltd.

New Industry Area Hecun Danzao Town
Nanhai Foshan City Guangdong China

TEL: +86-757-8180 8675

FAX: +86-757-8180 8685

E-mail: info@liteharbor.com

Website: www.liteharbor.com

Specifications subject to change w/o notice

Revision: Jan. 2015