RECESSED DOWNLIGH

AF6D-IA 6 inch Compact Fluorescent New Construction IC Airtight Recessed Housing

Catalog #		Prepared by		LiteHarbor
Project		Date		-
Notes				



6 inch Compact Fluorescent New Construction IC Airtight Recessed Housing

Housing


- 1) Die-formed aluminum for maximum heat dissipation and rust protection
- 2) Designed for New Construction installation
- 3) Housing can be installed in 1/2" to 1-3/8" thick ceilings.

Hanger Bar

- 1) Allow housing to be positioned and locked at any point within a 24" joist span.
- 2) Can be shortened for 12" joists
- 3) Can be positioned on long or short axis of the housing
- 4) Contain integral nail
- 5) Hanger fit onto T-bar spline for quick alignment

Junction Box

- 1) ETL listed for through branch wiring
- 2) 4 in-4 out J-box
- 3) Designed for straight through conduit runs
- 4) 1/2" and 3/4" romex wiring knockouts



Item No.:AF6D-IA	

A	Series
AF6D-IA	6"/ Compact Fluorescent New Construction
	IC Airtight Housing

В	Input Voltage	
	120V	
277	277V	

	C	Wattage
F.	32	CFL 32W



Liteharbor Lighting Technology Co., Ltd.

New Industry Area Hecun Danzao Town

Nanhai Foshan City Guangdong China

TEL: +86-757-8180 8675

FAX: +86-757-8180 8685

E-mail: info@liteharbor.com

Website: www.liteharbor.com

Specifications subject to change w/o notice

Revision: Jan. 2015

RECESSED DOWNLIGHT

Ballast D Color Temperature 1) Thermally protected 28K 2800k 2) Electronic ballast provides full light output and rated lamp life 35K 3500K 3) Flicker free and noise free operation and starting 50K 5000K

60K 6000K

5) Attached to junction box cover so it may be serviced from below the ceiling no tools required

Lamp & Socket

See Trim for max. wattage and lamp CRI>80% PF>0.9

4) End of lamp life protection is standard

Color Temperature:2800K-6500K

Listing

ETL listed for damp location W/Feed through

Other Special requirement please confirm with factory



Liteharbor Lighting Technology Co., Ltd.

New Industry Area Hecun Danzao Town

Nanhai Foshan City Guangdong China

TEL: +86-757-8180 8675

FAX: +86-757-8180 8685

E-mail: info@liteharbor.com

Website: www.liteharbor.com

Specifications subject to change w/o notice

Revision: Jan. 2015



RV6002 6 inch Vertical Reflector Self Flanged/White Ring



TEL: +86-757-8180 8675

FAX: +86-757-8180 8685

E-mail: info@liteharbor.com

Website: www.liteharbor.com

Specifications subject to change w/o notice

Revision: Jan. 2015