
BL4001-E LED Retrofit

| Catalog # | Prepared by | | LiteHarbor |
|-----------|-------------|--|------------|
| Project | Date | | |
| Notes | | | |




ORDER MATRIX | Example:BL4001-E




U 120-277V

C Dimmable Non-Dimmable DM Dimmable

D LED Available Cree Cree Citizen Citizen Epistar Epistar Seoul Seoul Osram Osram





Description

All-in-one LED retrofit trim designed to use with Liteharbor 4 inch recessed residential downlight. Provide 50000 hours of life at 70% lumen maintenance. No lead or mercury. Trim shipped with a medium base socket adapter whip.

LED Light Engine

Cree true white® technology available CRI>80% Color temperature: 2700K-5000K Rated for 50000 hours at 70% lumen output

Driver

Dedicated 120 volt driver Power factor >0.9 Dimmable to 10% with most brand dimmers Rated for 50 to 60Hz at 120V/277V input Produces less than 20% THD

Wattage

Input Power: 8W (+/-5%) Lumens: 400LM-560LM



Liteharbor Lighting Technology Co., Ltd. New Industry Area Hecun Danzao Town Nanhai Foshan City Guangdong China TEL: +86-757-8180 8675 FAX: +86-757-8180 8685 E-mail: info@liteharbor.com Website: www.liteharbor.com Specifications subject to change w/o notice Revision: Jan. 2015 Litebarb

ELumen Output400400 Lumen

560 560 Lumen

F Color Temperature

27K 2700K40K 4000K50K 5000K

Listing & Warranty

ETL listed to US and Canadian standards for wet locations 5-Year Limited Warranty

Litebarbe



Liteharbor Lighting Technology Co., Ltd. New Industry Area Hecun Danzao Town Nanhai Foshan City Guangdong China TEL: +86-757-8180 8675 FAX: +86-757-8180 8685 E-mail: info@liteharbor.com

Website: www.liteharbor.com Specifications subject to change w/o notice Revision: Jan. 2015