

BL6-001 6 Inch Baffle LED Retrofit

Catalog #		Prepared by		LiteHarbor
Project		Date		
Notes				









ORDER MATRIX | Example:BL6-001

А B С D F Е A Series BL6-001 6" LED Downlight Retrofit Input Voltage В 120V 277 277V U 120-277V C Dimmable Non-Dimmable DM Dimmable D LED Available Cree Cree Citizen Citizen Epistar Epistar Seoul Seoul Osram Osram

Description

All-in-one LED baffle retrofit trim designed to use with Liteharbor 5 inch recessed residential downlight. Provide 50000 hours of life at 70% lumen maintenance. No lead or mercury. Trim shipped with a medium base socket adapter whip.

LED Light Engine

Cree true white® technology available CRI>80% Color temperature: 2700K-5000K Rated for 50000 hours at 70% lumen output

Driver

Dedicated 120 volt driver Power factor >0.9 Dimmable to 10% with most brand dimmers Rated for 50 to 60Hz at 120V/277V input Produces less than 20% THD

Wattage

Input Power: 16W (+/-5%) Lumens: 1100LM/1250LM



Liteharbor Lighting Technology Co., Ltd. New Industry Area Hecun Danzao Town Nanhai Foshan City Guangdong China TEL: +86-757-8180 8675 FAX: +86-757-8180 8685 E-mail: info@liteharbor.com Website: www.liteharbor.com Specifications subject to change w/o notice Revision: Jan. 2015

ED RETROFIT

Itcharb

E Lumen Output

1100 1100 Lumen 1250 1250 Lumen Listing & Warranty ETL listed to US and Canadian standards for wet locations 5-Year Limited Warranty

F Color Temperature

27K 2700K

40K 4000K 50K 5000K

Litcharbe



Liteharbor Lighting Technology Co., Ltd. New Industry Area Hecun Danzao Town Nanhai Foshan City Guangdong China TEL: +86-757-8180 8675 FAX: +86-757-8180 8685 E-mail: info@liteharbor.com Website: www.liteharbor.com Specifications subject to change w/o notice Revision: Jan. 2015