



BL6-001-1 LED Retrofit

Catalog #		Prepared by	LiteHarbor
Project		Date	
Notes			



ORDER MATRIX | Example:BL6-001-1



LED RETROFIT

<u>A</u>	<u>B</u>	<u>C</u>	<u>D</u>	<u>E</u>	<u>F</u>
<hr/>					
A	Series				
BL6-001-1	6" LED Downlight Module				
<hr/>					
B	Input Voltage				
	120V				
277	277V				
U	120-277V				
<hr/>					
C	Dimmable				
	Non-Dimmable				
DM	Dimmable				
<hr/>					
D	LED Available				
Cree	Cree				
Citizen	Citizen				
Epistar	Epistar				
Seoul	Seoul				
Osram	Osram				

Description

All-in-one LED retrofit trim designed to use with Liteharbor 6 inch recessed residential downlight. Provide 50000 hours of life at 70% lumen maintenance. No lead or mercury. Trim shipped with a medium base socket adapter whip.

LED Light Engine

Source LED 16W
Cree true white® technology available
Color temperature: 2700K-6500K
Rated for 50000 hours at 70% lumen output

CRI	80%	90%
Luminous flux	1250lm	1100lm
Light effect	78lm/w	68lm/w

Driver

Dedicated 120 volt driver
Power factor >0.98
Dimmable to 10% with most brand dimmers
Rated for 50 to 60Hz at 120V/277V input
Produces less than 20% THD



Liteharbor Lighting Technology Co., Ltd.
New Industry Area Hecun Danzao Town
Nanhai Foshan City Guangdong China

TEL: +86-757-8180 8675
FAX: +86-757-8180 8685
E-mail: info@liteharbor.com

Website: www.liteharbor.com
Specifications subject to change w/o notice
Revision: Jan. 2015

E	Lumen Output
1100	1100 Lumen
1250	1250 Lumen

F	Color Temperature
27K	2700K
30K	3000K
65K	6500K

Listing & Warranty

ETL listed to US and Canadian standards for wet locations

5-Year Limited Warranty



LED RETROFIT



Liteharbor Lighting Technology Co., Ltd.

New Industry Area Hecun Danzao Town
Nanhai Foshan City Guangdong China

TEL: +86-757-8180 8675

FAX: +86-757-8180 8685

E-mail: info@liteharbor.com

Website: www.liteharbor.com

Specifications subject to change w/o notice

Revision: Jan. 2015