





**BL4-002-B**  
**4" High Performance Remodel**  
**LED Recessed Downlight Series**

<b>Catalog #</b>		<b>Prepared by</b>	LiteHarbor
<b>Project</b>		<b>Date</b>	
<b>Notes</b>			



RECESSED DOWNLIGHT

**4 Inch High Performance Remodel LED Recessed Downlight Series**

**Order Matrix** | Example: BL4-002-B-A-L12-30K-WH

A B C D E F G

**Description**

4 inch Remodel LED recessed fixtures with round apertures offer energy-efficient, precision lighting for accent, task, or wall wash applications.

The innovative design allows the LED to be positioned closer to the aperture for maximum light output and efficiency or higher to minimize glare and flash on the trim.

**Features**

Separable rotating reflector design makes it easy for replacement.

High grade diffuser provides uniform light

driver can achieve high power factor and conversion efficiency, constant current output.

Achieve 3 functions through changing screw setting places and replacing matched reflectors.

**Item No.:BL4-002-B**

A	Series
BL4-002-B	4" Recessed Downlight

B	Functions
	Vertical Downlight
A	Adjustable Downlight
W	Wall Wash Downlight

C	Input Voltage
	120V
230	230V
277	277V
U	90-305VAC



**Liteharbor Lighting Technology Co., Ltd.**  
 New Industry Area Hecun Danzao Town  
 Nanhai Foshan City Guangdong China

TEL: +86-757-8180 8687  
 FAX: +86-757-8180 8685  
 E-mail: info@liteharbor.com

Website: www.liteharbor.com  
 Specifications subject to change w/o notice  
 Revision: May, 2016

### LED Light Engine

Optional branded COB LED chips

Input AC 120V/230V/277V at 50/60Hz ( 90-305V is optional.)

Color Temperature: 2700K-5000K

PF > 0.98

Dimmable options: NONE/TRIAC

This energy efficient downlight uses 15-watts max. and is comparable to a 60-watt Halogen light bulb.

LED mounted to die-cast / extruded aluminum heat sink w/ active cooling

50,000 hours average rated life at 70% output

### PACKAGE

Inner Box Size: 165x135x155mm

CTN Size: 425x345x335mm

12 PCS/CTN

D	Wattage
L10	LED 10W
L12	LED 12W
L15	LED 15W

E	Lumen Output
800	800 Lumen
1000	1000 Lumen
1300	1300 Lumen

F	Color Temperature
27K	2700K
30K	3000K
35K	3500K
40K	4000K
50K	5000K

G	Finish
WH	White
CL	Clear
HZ	Haze



Vertical



Adjustable & Wall Wash



**Liteharbor Lighting Technology Co., Ltd.**

New Industry Area Hecun Danzao Town

Nanhai Foshan City Guangdong China

TEL: +86-757-8180 8687

FAX: +86-757-8180 8685

E-mail: info@liteharbor.com

Website: www.liteharbor.com

Specifications subject to change w/o notice

Revision: May. 2016



RECESSED DOWNLIGHT