PENDENT COB **BLUETOOTH MULTIPLE DOWNLIGHT**

Catalog :	#	Prepar	ed by	LiteHarbor
Project		Date		
Notes	•			





G4012-M-COB

ORDER MATRIX | Example: G401X-M-COB

<u>A</u>	В	<u>C</u>	D	E
	A	Series		
G4011-M-0	COB	1 Lamp		
G4012-M-0	СОВ	2 Lamp		
G4013-M-0	СОВ	3 Lamp		
G4014-M-0	СОВ	4 Lamp		

В	Watt
10	10W/Lamp

C	Input Voltage
120	120V
277	277V
U	120V-277V

Description

Mini COB LED Multiple Spots for remodeling and new construc applications for residential and commercial environments. The Multiple Spots are marketed as complete units including the housing and trim. Available as one, two and three-light configurations, each spot is individually adjustable and provides a 30-degree visual cutoff for glare control.

Features

- This product, all-metal material, thick, stable, combined with Bluetooth Speaker, even more stylish and beautiful.
- Pendent and ceiling mounting series multiple downlight equipped with one lamp, two lamp, three lamp and four lamp.
- Each lamp can up and down around the rotation.
- 30 °vertical tilt, 360 °horizontal rotation. 30 °anti glare control
- Whether it is ceiling installation or pendent installation, it have played a very good decorative effect.
- Light bulbs can be directly removed from the bottom without the tool, no need to remove the lamp down and then replace, save time and effort.
- Can add Bluetooth stereo, the light combination with the music, add life fun.



Liteharbor Lighting Technology Co., Ltd.

New Industry Area Hecun Danzao Town Nanhai Foshan City Guangdong China

TEL: +86-757-8180 8675

FAX: +86-757-8180 8685

E-mail: info@liteharbor.com

Website: www.liteharbor.com

Specifications subject to change w/o notice

Revision: Mar. 2017

PENDENT MULTIPLE DOWNLIGHT

D	Color Temperature	Data
27	2700K	Light Source: COB
30	3000K	Power Factor: >0.98
35	3500K	Material: Gauge Steel
40	4000K	Frequency: 50/60Hz
50	5000K	CRI: Ra>80/90

Е	Luminous Efficiency
750	750LM/Lamp

Dimming

Dimmable to 10% with most brand dimmers.

Construction

Trim and housing are constructed of Gauge Steel.

Mounting

Ceilling mount or pendent mount.

Warranty

Five Year Limited Warranty.

Precautions

To ensure proper operation of the product, make sure that the voltage at the time of use is within the indicated voltage range. Please disconnect the power supply when installing and disassembling the product to avoid the risk of electric shock.

Do not use this product in high humidity or dusty environments.

Do not look at the LED light source for a long time, high intensity light source may cause eye damage.

When you find the following questions, please contact the ualified electrician for repair services:

The product produces a foul smell, an abnormal sound, or an unusual flicker.

Shell damage, foreign invasion of internal.



Liteharbor Lighting Technology Co., Ltd.New Industry Area Hecun Danzao Town

Nanhai Foshan City Guangdong China

TEL: +86-757-8180 8675

FAX: +86-757-8180 8685

E-mail: info@liteharbor.com

Website: www.liteharbor.com

Specifications subject to change w/o notice

Revision: Mar. 2017