

Die-cast aluminum LED Pendant Light

Catalog #		Prepared by	LiteHarbor
Project		Date	
Notes			



PD-BL-FM3C



PD-BL-FM3C-S



PD-BL-SFM3C



PD-BL-SFM3C-S

ORDER MATRIX | Example:PD-BL-FM3C

A B C D E F G

A	Series
PD-BL-FM3C	Round LED Pendant Mount
PD-BL-SFM3C	Square LED Pendant Mount
PD-BL-FM3C-S	Round LED Suspended Mount
PD-BL-SFM3C-S	Square LED Suspended Mount

B	Input Voltage
	110V
277	277V

C	Dimmable
	Non-Dimmable
DM	Dimmable

D	LED Available
Cree	Cree
Citizen	Citizen
Epistar	Epistar
Seoul	Seoul
Osram	Osram

Description

An architecturally pleasing, easy to install and low profile slim LED pendant mount round and square aperture downlighting.

Slim line, light weight and sleek look, provides more uniform light and an instant on.

It is a low profile pendant light intended for ceiling applications.

Applications

Slim LED Pendant Mount ceiling light is characterized by a completely flat lens with a narrow flange, giving it an architecturally pleasing look.

Can used for all residential and commercial and retail or hospitality high ceiling applications.

Features

Decorative LED Pendant Ceiling Light fixture

80% energy savings

Damp location listed

Easy to install

Die cast aluminum material



LED PENDANT LIGHT



Liteharbor Lighting Technology Co., Ltd.

New Industry Area Hecun Danzao Town
Nanhai Foshan City Guangdong China

TEL: +86-757-8180 8675

FAX: +86-757-8180 8685

E-mail: info@liteharbor.com

Website: www.liteharbor.com

Specifications subject to change w/o notice

Revision: Apr. 2017

E	Color Temperature
27K	2700K
40K	4000K
50K	5000K
60K	6000K
	Tunable (3000K, 4000K, 5000K, choose any 2 of them)

F	Emergency System
	Without Emergency Battery Backup
EM	With Emergency Battery Backup

G	Length
6	6"
12	12"
18	18"
24	24"
36	36"
48	48"

LED Light Engine

LED 3030
120V / 277V
10.5W/13.5W/18.5W=42.5W
100lm/W
TRIAC Dimmable

Finish

Available in White, Brushed Nickel, and Bronze

Usage


Residential
Office
Retail
Hospitality

Listing & Warranty


3-Year Limited Warranty
ETL listed for North America market!

Dimensions

Ø: 9"xH:1"



Light Distribution



Liteharbor Lighting Technology Co., Ltd.

New Industry Area Hecun Danzao Town
Nanhai Foshan City Guangdong China

TEL: +86-757-8180 8675

FAX: +86-757-8180 8685

E-mail: info@liteharbor.com

Website: www.liteharbor.com

Specifications subject to change w/o notice

Revision: Apr. 2017



Emergency

24 hours recharge time
>90 minute operation from battery
over-charge/discharge protection


Dimensions

Ø: 9"xH:2 3/16"

Ordering Guide

Series	Input Voltage	Dimmable	CCT	Finish	Emergency System
<input type="checkbox"/> PD-BL-FM3C	<input type="checkbox"/> 110V	<input type="checkbox"/> Non-Dimmable	<input type="checkbox"/> 2700K	<input type="checkbox"/> White	<input type="checkbox"/> Without Emergency
<input type="checkbox"/> PD-BL-SFM3C	<input type="checkbox"/> 277V	<input type="checkbox"/> Dimmable	<input type="checkbox"/> 3000K	<input type="checkbox"/> Bronze	Battery Backup
<input type="checkbox"/> PD-BL-FM3C-S			<input type="checkbox"/> 4000K	<input type="checkbox"/> Satin Nickel	<input type="checkbox"/> With Emergency
<input type="checkbox"/> PD-BL-SFM3C-S			<input type="checkbox"/> 5000K		Battery Backup
			<input type="checkbox"/> 6000K		
			<input type="checkbox"/> Tunable		

(3000K, 4000K, 5000K, choose any 2 of them)



LED PENDANT LIGHT



Liteharbor Lighting Technology Co., Ltd.

New Industry Area Hecun Danzao Town
Nanhai Foshan City Guangdong China

TEL: +86-757-8180 8675

FAX: +86-757-8180 8685

E-mail: info@liteharbor.com

Website: www.liteharbor.com

Specifications subject to change w/o notice

Revision: Apr. 2017