

DG5213 LED FLOOD LIGHT





DESCRIPTION


- Ultra-thin streamlined external light design and LED structure features organically combined, the appearance is simple.
- 4mm tempered clear glass, light transmittance up to 95%, reduce the light loss.
- High density die casting aluminum lamp body with reasonable heat dissipation design to ensure the service life of lamps.
- Adopt brand LED light source.
- Outdoor professional static outdoor plastic powder sprayed on surface, anti-UV, anti-corrosion and weather resistance is strong.
- Lighting structure, electrical safety compliance with EN60598 GB7000 standard requirements.
- Electric shock protection: Class I
- IP rating: IP66


UNIQUE TOUCH SWITCH DIMMING FUNCTION:

3CCT (3000K/4500K/6000K).

UNIQUE OUTDOOR WALL SWITCH COLOR TEMPERATURE CONTROL FUNCTION: 3CCT (3000K/4500K/6000K)

ORDER MATRIX:





H=31mm







▲ New Industry Area, Hecun, Danzao Town, Nanhai,Foshan City, China
▼ 0757-8180-8675
■ www.liteharbor.com
■ info@liteharbor.com

ite





APPLICATION:

Suitable for factories, gymnasiums, wharfs, billboards, buildings, lawn, gardening design and other lighting and decorative lighting places.

ORDERING GUIDE

Model	Input Voltage	Light Source	Power	Luminous Efficiency	Optional light	Luminous Flux	Dimensions
DG5213	AC120V	24 PCS	10W	>100lm/W	120	1000lm	112.5X216X31mm
DG5213A	AC120V	48 PCS	20W	>100lm/W	120	2000lm	112.5X216X31mm

OTHER PARAMETERS

Applicable Ambient Temperature	- 3050°C					
Total Harmonic Distortion	< 15%					
Working Temperature	RH10%-90%					
CRI	Ra>75-95 optional					
CCT	3000K 4500K 6000K					
IP Rating	IP 66					
Life Span	>20000h/>30000h/>50000h are optional					
Power Factor	> 0.95					
Frequency Range	50-60Hz					
Electric-shock safeguard	CIASS I					
Mounting	In-ground Mounting / Suspension Mounting / Tree Hanging Mounting					

0757-8180-8675





