

DG5215LED FLOOD LIGHT









In-ground Mounting



Suspension Mounting



Tree Hanging Mounting

DESCRIPTION

- Ultra-thin streamlined external light design and LED structure features organically combined, the appearance is simple.
- 4mm tempered clear glass, light transmittance up to 95%, reduce the light loss.
- High density die casting aluminum lamp body with reasonable heat dissipation design to ensure the service life of lamps.
- Adopt brand LED light source.
- Outdoor professional static outdoor plastic powder sprayed on surface, anti-UV, anti-corrosion and weather resistance is strong.
- Lighting structure, electrical safety compliance with EN60598 GB7000 standard requirements.
- Electric shock protection: Class I
- IP rating: IP66


UNIQUE TOUCH SWITCH DIMMING FUNCTION:

3CCT (3000K/4500K/6000K).

UNIQUE OUTDOOR WALL SWITCH COLOR TEMPERATURE CONTROL FUNCTION:

3CCT (3000K/4500K/6000K)

ORDER MATRIX:



2000 V CONTROL OF CONT

L=321mm

W=421mm

H=55mm







🖪 New Industry Area, Hecun, Danzao Town, Nanhai, Foshan City, China

C 0757-8180-8675

www.liteharbor.com

info@liteharbor.com





APPLICATION:

Suitable for factories, gymnasiums, wharfs, billboards, buildings, lawn, gardening design and other lighting and decorative lighting places.

ORDERING GUIDE

Model	Input Voltage	Light Source	Power	Luminous Efficiency	Optional light	Luminous Flux	Dimensions
DG5215	AC120V	224 PCS	150W	>100lm/W	120	15000lm	321X421X55mm
DG5215A	AC120V	448 PCS	200W	>100lm/W	120	20000lm	321X421X55mm

OTHER PARAMETERS

Applicable Ambient Temperature	- 3050°C						
Total Harmonic Distortion	< 15%						
Working Temperature	RH10%-90%						
CRI	Ra>75-95 optional						
CCT	3000K	4500K	6000K				
IP Rating	IP 66						
Life Span	>20000h/>30000h/>50000h are optional						
Power Factor	> 0.95						
Frequency Range	50-60Hz						
Electric-shock safeguard	CIASS I						
Mounting	In-ground Mounting / Suspension Mounting / Tree Hanging Mounting						







