



LED SPOTLIGHT

Catalog #		Prepared by	LiteHarbor
Project		Date	
Notes			



LED Surface Mounted Downlight

Features

- This is a circular surface-mounted spotlight that incorporates modern aesthetics. It has a beautifully curved shape, scientific light distribution, good light output, uniform light output, high efficiency and energy saving.
- The light source can be adjusted 25 °vertically and 360 °horizontally to direct the beam in any direction to meet your diverse lighting needs.
- The beam angle can be 12 °, 24 °, and suitable lamps can be selected according to actual needs to provide professional lighting.
- Patented convenient installation structure for quick and easy installation.
- Dimming: Non-Dimming/TRIAC Dimming.
- Adaptable 3" and 4" embedded box mounting.

Specifications

Lamp Body: Made of die-cast aluminum, the material is light and has good heat dissipation.

Power Supply: Constant current power supply, long life, low electromagnetic interference, low energy consumption, high performance, short circuit and overcurrent protection.

Light Source: Using big brand COB lamp beads, color rendering index 80+, 90+ are optional, a variety of color temperature options (3000K, 4000K, 5000K, 6500K).

Mounting plate: Patent structure.

LED SPOTLIGHT



Liteharbor Lighting Technology Co., Ltd.

New Industry Area Hecun Danzao Town
Nanhai Foshan City Guangdong China

TEL: +86-757-8180 8687

FAX: +86-757-8180 8685

E-mail: info@liteharbor.com

Website: www.liteharbor.com

Specifications subject to change w/o notice

Revision: Jun. 2018

Applications

Apply to automotive and parking, education, government, healthcare, hospitality, offices and banks, religious, retail.

Parameter List

Watt	8W/lamp	10W/lamp
Voltage	AC 120V/230V/277V/120V-277V	
Frequency	50/60 Hz	
PF	>0.9	
Dimming	Non-Dimming/TRIAC Dimming	
CRI	80+/90+	
CCT	3000/4000/5000/6000K	

Listing / Warranty

ETL listed to US and Canadian standards for damp location W/Feed through.

5 Year Limited Warranty.

Packing

Inner Box: 250*130*115 mm 1 PC/Box

Carton: 51.5*40.5*25.5 cm 12 boxes/Carton

Ordering Guide

Series	Lumen	CCT	CRI	Voltage	Dimming
<input type="checkbox"/> G4012-D1-E8	<input type="checkbox"/> 1260lm	<input type="checkbox"/> 2700K	<input type="checkbox"/> 80+	<input type="checkbox"/> AC 120V	<input type="checkbox"/> Non-Dimming
2 Lamps Surface Mounted	<input type="checkbox"/> 1600lm	<input type="checkbox"/> 3000K	<input type="checkbox"/> 90+	<input type="checkbox"/> AC 230V	<input type="checkbox"/> TRIAC Dimming
LED Spotlight		<input type="checkbox"/> 4000K		<input type="checkbox"/> AC 277V	
		<input type="checkbox"/> 5000K		<input type="checkbox"/> AC120-277V	
		<input type="checkbox"/> 6000K			

Finish

- Black
- White



Liteharbor Lighting Technology Co., Ltd.

New Industry Area Hecun Danzao Town

Nanhai Foshan City Guangdong China

TEL: +86-757-8180 8687

FAX: +86-757-8180 8685

E-mail: info@liteharbor.com

Website: www.liteharbor.com

Specifications subject to change w/o notice

Revision: Jun. 2018

