

LED CEIL

BL12-FM11 LED CEILING LIGHT

Catalog #	Prepared by	LiteHarbor
Project	Date	
Notes		







12 Inch Round Shape Flush Mounted LED Ceiling Light

Description

An architecturally pleasing, easy to install and low profile slim LED instant mount round and square aperture downlighting. Slim line, light weight and slook look, provides more uniform light and an instant on. It is a low profile downlight intended for ceiling or wall mounted applications. This luminaire offers the appearance of a recessed downlight but is actually surface mounted.

Features

- LED 12 inch flush mounted.
- Decorative flush mounted LED fixture.
- 24W equal to a traditional 100W lamp.
- 84% energy savings.
- Damp location listed.
- Mounts directly to 3" and 4" junction boxes.
- Easy to install.

Applications

- Slim LED Flush Mount Downlight is characterized by a completely flat lens with a narrow flange, giving it an architecturally pleasing look.
- This downlighting solution offers an affordable alternative to Air-Seal IC recessed housings or Fire-Rated boxes, reducing material and installation costs.
- Suitable for jewelry stores, boutiques, luxury goods stores, shopping malls and other places that require concentrated lighting and accent lighting.



Liteharbor Lighting Technology Co., Ltd.
New Industry Area Hecun Danzao Town
Nanhai Foshan City Guangdong China

TEL: +86-757-8180 8687

FAX: +86-757-8180 8685

E-mail: info@liteharbor.com

Website: www.liteharbor.com

Specifications subject to change w/o notice

Revision: Jul. 2019

Listing / Warranty


ETL listed to US and Canadian standards for damp location W/Feed through.


3 Year Limited Warranty.

Parameter

Voltage	AC 120V		
Frequency	60 Hz		
Watt	24W		
Dimmable	Non-dimming/TRIAC		
CCT	2700-6000K		
Material	Aluminum		
Finish	White/Black		

Dimensions







Liteharbor Lighting Technology Co., Ltd.New Industry Area Hecun Danzao Town
Nanhai Foshan City Guangdong China

TEL: +86-757-8180 8687 FAX: +86-757-8180 8685

E-mail: info@liteharbor.com

Website: www.liteharbor.com

Specifications subject to change w/o notice

Revision: Jul. 2019



Ordering Guide

Series/Lumen	Input Voltage	CCT	Dimming	
□ BL12-FM11/19001m	120V	□ 2700K	□ Non-dimming	
LED Ceiling Light		□ 3000K	□ TRIAC Dimming	
		□ 4000K		
		□ 5000K		
		□ 6000K		
		□ Tunable		
		*(3000K, 4000K, 5000K, choose any 2 of them)		
CRI	Finish	Emergen	cy System	
□ 80+	White	□ Without E	hout Emergency Battery Backup	
□ 90+	Black	□ With Emer	rgency Battery Backup	
	Brown			
*Other special requirements	 an Company with a sum for a to			



TEL: +86-757-8180 8687

FAX: +86-757-8180 8685 E-mail: info@liteharbor.com Website: www.liteharbor.com

Specifications subject to change w/o notice

Revision: Jul. 2019

Other special requirements please confirm with our factory