# BEL2014-A-01 LED EYEBALL DOWNLIGHT

Catalog #	Prepared by LiteHarbo
Project	Date
Notes	



## 2 Inch Round Shape LED Eyeball Multiple Downlight wiht 4 Lamps

#### Description

This is a 2" rotatable LED eyeball muiltple downlight allow for you to set the ambiance in your space, a full range of repositioning to highlight your decoration, giving you everything needed to install this beautiful, ultra thin recessed lighting solution.

#### Features

- Swivel eyball trim allows the flexibility focus light on a specifc area and create the ambiance you desire.
- Protected LED driver performs at 120V/120~277V.
- This fixture is built to last with maintenance-free energy efficient LEDs.
- Available in 1, 2, 3, 4 lamps.
- Beam Angle: 30/60 Degree.
- Suitable for damp location.

#### Applications

Apply to automotive and parking, education, government, healthcare, hospitality, offices and banks, religious, retail.



Liteharbor Lighting Technology Co., Ltd.TEL: +86-757-8180 8687Website: www.liteharbor.comNew Industry Area Hecun Danzao TownFAX: +86-757-8180 8685Specifications subject to change w/o noticeNanhai Foshan City Guangdong ChinaE-mail: info@liteharbor.comRevision: Aug. 2019

## **Specification**


Watt	6W/lamp	
	1	
Voltage	AC 120V/120~277V	
Driver	Liteharbor	
PF	>0.9	
Dimming	Dimmable	
Lumen	480lm/lamp	
Light Source	COB	
CRI	80+/90+	
Beam Angle	30D/60D	
ССТ	2700K-5000K	
Material	Aluminum	
Finish	White/Black	


## Listing / Warranty

ETL listed to US and Canadian standards for damp location W/Feed through.

3 Year Limited Warranty.

#### Dimensions







Liteharbor Lighting Technology Co., Ltd. New Industry Area Hecun Danzao Town Nanhai Foshan City Guangdong China TEL: +86-757-8180 8687 FAX: +86-757-8180 8685 E-mail: info@liteharbor.com Website: www.liteharbor.com Specifications subject to change w/o notice Revision: Aug. 2019 Litchurbon

# **Ordering Guide**

Series	Voltage	Watt	ССТ	Finish
□ BEL2014-A-01	□ 120V	□ 6W/lamp	□ 2700K	□ Black
2" LED Eyeball	□ 120~277V		□ 3000K	□ White
Multiple Downlight			□ 4000K	
			□ 5000K	
CRI	Beam Angle			

CRI	Beam Angl
80+	30°
90+	60°

Litcharbo



**Liteharbor Lighting Technology Co., Ltd.** New Industry Area Hecun Danzao Town Nanhai Foshan City Guangdong China TEL: +86-757-8180 8687 FAX: +86-757-8180 8685 E-mail: info@liteharbor.com

Website: www.liteharbor.com Specifications subject to change w/o notice Revision: Aug. 2019