

# EXL001-R LED Exit & Emergency Light

|                  |  |                    |            |
|------------------|--|--------------------|------------|
| <b>Catalog #</b> |  | <b>Prepared by</b> | LiteHarbor |
| <b>Project</b>   |  | <b>Date</b>        |            |
| <b>Notes</b>     |  |                    |            |



### Order Matrix:

    A    B    C    D    E    F    G    H    

**Item No.: EXL001-R**

|          |            |
|----------|------------|
| A        | Series     |
| EXL001-R | Exit Light |

|   |           |
|---|-----------|
| B | Sign      |
|   | Exit Sign |
| R | Running   |

|     |               |
|-----|---------------|
| C   | Input Voltage |
|     | 120V          |
| 347 | 347V          |

|    |             |
|----|-------------|
| D  | Face Q'ty   |
| SF | Single Face |
| DF | Double Face |

|    |                |
|----|----------------|
| E  | Battery Backup |
|    | Battery Backup |
| AC | AC Only        |

### Description

- Maintained and non-maintained modes of operation
- High resistance polycarbonate clear cover and Injection ABS housing
- Low energy consumption and heat dissipation - save up to 70% on energy consumption\*
- Unique single LED maintained exit sign
- Long life LED light source - up to 50,000 hours
- Both ceiling and wall mounted versions available
- Both the wall mount and ceiling mount diffusers include all directional pictograms, such as "Running Man" and "EXIT"
- Large terminal block for ease of connection
- Low cost maintenance
- Available in White, Silver and Black body
- Available in individual parts or as an All-in-one box solution
- Base mounting hole pattern compatible with most common exit signs

### Electrical

- Universal Voltage Input 120-347 VAC 50/60Hz
- Universal 2 wire DC input 6VDC/12VDC/24VDC



EXIT & EMERGENCY LIGHT



**Liteharbor Lighting Technology Co., Ltd.**  
New Industry Area Hecun Danzao Town  
Nanhai Foshan City Guangdong China

TEL: +86-757-8180 8675  
FAX: +86-757-8180 8685  
E-mail: info@liteharbor.com

Website: www.liteharbor.com  
Specifications subject to change w/o notice  
Revision: Jan. 2015

### Lamp

Exit face illumination is provided by energy savings, long life red or green LEDs.  
Energy efficient – consumes less than 2.5 Watts in AC mode and only 1W in DC-remote

### Battery

- Sealed Nickel Cadmium
- Maintenance-free, Long-life
- Full recharge time, 24 hrs. (Max.)

### Warranty

5-Year Limited warranty

| F  | Housing Color |
|----|---------------|
| BK | Black         |
| WH | White         |

| G  | Letter Color |
|----|--------------|
| RD | Red          |
| GN | Green        |

| H   | Arrow Direction |
|-----|-----------------|
|     | No indicators   |
| LA  | Left indicator  |
| RA  | Right indicator |
| UA  | Up indicator    |
| DA  | Down indicator  |
| URA | 45 °up right    |
| DRA | 45 °down right  |
| ULA | 45 °up left     |
| DLA | 45 °down left   |



**Liteharbor Lighting Technology Co., Ltd.**

New Industry Area Hecun Danzao Town  
Nanhai Foshan City Guangdong China

TEL: +86-757-8180 8675

FAX: +86-757-8180 8685

E-mail: info@liteharbor.com

Website: www.liteharbor.com

Specifications subject to change w/o notice

Revision: Jan. 2015